



尺寸

量程	H	H1	H2	H3	H4	L	L1	L2	L3	L4	L5	W	W1	T
651AA:														
kg/mm														
5-100	65.5	63.0	56.0	13.6	25.4	118.0	19.1	65.0	7.5	32.0	96.5	30.0	25.5	M6X1 深 19
lb/inches (由上述尺寸转换)														
11.0-220.5	2.58	2.48	2.21	0.54	1.00	4.65	0.75	2.56	0.30	1.26	3.80	1.18	1.00	M6X1 深 0.75
651AAUN:														
kg/mm														
5-100	65.5	63.0	56.0	13.6	25.4	118.0	19.1	65.0	7.5	32.0	96.5	30.0	25.5	1/4-20UNC-2B 深 19
lb/inches (由上述尺寸转换)														
11.0-220.5	2.58	2.48	2.21	0.54	1.00	4.65	0.75	2.56	0.30	1.26	3.80	1.18	1.00	1/4-20UNC-2B 深 0.75

技术参数

灵敏度	2.0 mV/V ± 10%	额定激励电压	10V (15V 最大)
零位输出	±0.02 mV/V	推荐最大台面尺寸	400×400 mm
非线性	< ±0.017%	绝缘阻抗	>2 [50V DC] GΩ
重复性	< ±0.017%	正常工作温度范围	-10°C - 40°C / 14°F - 104°F
滞后误差	< ±0.017%	安全极限载荷	150% 满量程
蠕变	< ±0.023%	破坏极限载荷	300% 满量程
输入阻抗	415Ω ± 15	密封方式	密封 / IP66
输出阻抗	350Ω ± 3	接线方式	Exc+ 红 Exc- 黑 Sig+ 绿 Sig- 白 屏蔽线
原材料	铝合金		

货 号*

651AA		
量程	货号	毛重(kg)
5kg	651AA-5kg	0.5
10kg	651AA-10kg	0.5
15kg	651AA-15kg	0.5
30kg	651AA-30kg	0.5
50kg	651AA-50kg	0.5
90kg	651AA-90kg	0.5
100kg	651AA-100kg	0.5

货 号*

651AAUN		
量程	货号	毛重(kg)
5kg	651AAUN-5kg	0.5
10kg	651AAUN-10kg	0.5
15kg	651AAUN-15kg	0.5
30kg	651AAUN-30kg	0.5
50kg	651AAUN-50kg	0.5
90kg	651AAUN-90kg	0.5
100kg	651AAUN-100kg	0.5

* ATEX, FM, IECEx 认证版本货号带有“-Ex”后缀